

# UK Declaration of Performance



No. 32-1000\_001-2025

1. Unique identification of the product-type
2. Type, batch or serial number or other element allowing identification of the construction product
3. Intended use or uses of the construction product as foreseen by the manufacturer
4. Name, registered trade name or trade mark and contact address of the manufacturer
5. System of assessment and verification of constancy of the construction products
6. Name and identification number of the Approved Body concerning a construction product covered by a designated standard
7. Declared performance according to

## Single Skin Steel Profiled Sheet

### 32/1000 Box Profile in Over Purlin / Under Purlin Configurations

Single skin steel profiled sheet for use as cladding in roofs or walls of buildings in accordance with EN 14782:2006

**BRIARWOOD PRODUCTS LTD,**  
**Briarwood Business Park,**  
**Commerce Way,**  
**Walrow Industrial Estate,**  
**Highbridge, Somerset, TA9 4AG**

### AVCP System 4

The manufacturer has taken responsibility for initial type testing and implementation of factory production control, in accordance with AVCP System 4

### BS EN 14782:2006

Self-supporting metal sheet for roofing, external cladding and internal lining - Product specification and requirements.

See the below tables showcasing the performances of each product using materials which we roll from.

UK CA		UK CA		UK CA		UK CA	
BRIARWOOD PRODUCTS LTD, Briarwood Business Park, Commerce Way, Walrow Industrial Estate, Highbridge, Somerset, TA9 4AG		BRIARWOOD PRODUCTS LTD, Briarwood Business Park, Commerce Way, Walrow Industrial Estate, Highbridge, Somerset, TA9 4AG		BRIARWOOD PRODUCTS LTD, Briarwood Business Park, Commerce Way, Walrow Industrial Estate, Highbridge, Somerset, TA9 4AG		BRIARWOOD PRODUCTS LTD, Briarwood Business Park, Commerce Way, Walrow Industrial Estate, Highbridge, Somerset, TA9 4AG	
EN 14782:2006 Self supporting steel sheeting for roofing, external cladding and internal lining Profile: 32/1000, Thickness: 0.50, Class 1, S220GD + Z225 or AZ150 Side 1: Polyester 25µm, Side2: EP7µm, EN508-1		EN 14782:2006 Self supporting steel sheeting for roofing, external cladding and internal lining Profile: 32/1000, Thickness: 0.70, Class 1, S220GD + Z225 or AZ150 Side 1: Polyester 25µm, Side2: EP7µm, EN508-1		EN 14782:2006 Self supporting steel sheeting for roofing, external cladding and internal lining Profile: 32/1000, Thickness: 0.50, Class 1, S220GD + Z225 or AZ150 Side 1: Generic Plastisol 200µm, Side2: EP7µm, EN508-1		EN 14782:2006 Self supporting steel sheeting for roofing, external cladding and internal lining Profile: 32/1000, Thickness: 0.70, Class 1, S220GD + Z225 or AZ150 Side 1: Generic Plastisol 200µm, Side2: EP7µm, EN508-1	
<b>Mechanical Resistance:</b> Resistance to concentrated force	<b>Roof</b> 1.2N at 2.4m span	<b>Wall</b> 1.2N at 2.4m span	<b>Mechanical Resistance:</b> Resistance to concentrated force	<b>Roof</b> 1.2N at 2.4m span	<b>Wall</b> 1.2N at 2.4m span	<b>Mechanical Resistance:</b> Resistance to concentrated force	<b>Roof</b> 1.2N at 2.4m span
<b>Water Permeability:</b>	No Performance Declared	No Performance Declared	<b>Water Permeability:</b>	No Performance Declared	No Performance Declared	<b>Water Permeability:</b>	No Performance Declared
<b>Dimensional Change:</b>	No Performance Declared	No Performance Declared	<b>Dimensional Change:</b>	No Performance Declared	No Performance Declared	<b>Dimensional Change:</b>	No Performance Declared
<b>Release of Regulated Substances:</b>	No Performance Declared	No Performance Declared	<b>Release of Regulated Substances:</b>	No Performance Declared	No Performance Declared	<b>Release of Regulated Substances:</b>	No Performance Declared
<b>External Fire Performance:</b>	Broof t4	Broof t4	<b>External Fire Performance:</b>	Broof t4	Broof t4	<b>External Fire Performance:</b>	Broof t4
<b>Reaction to Fire:</b>	C-s3, d0	C-s3, d0	<b>Reaction to Fire:</b>	C-s3, d0	C-s3, d0	<b>Reaction to Fire:</b>	C-s3, d0
<b>Durability:</b>	No Performance Declared	No Performance Declared	<b>Durability:</b>	No Performance Declared	No Performance Declared	<b>Durability:</b>	No Performance Declared

The performance of the product(s) identified in point 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance issued under the sole responsibility of the manufacturer identified in point 4.

**Oliver Janes - CEO**  
**Somerset, England, UK**  
**Date signed: 3/11/2025**