
EAVES FLASHING TECHNICAL DATASHEET

WOODGRAIN · 165 x 175 x 25 x 25 · 0.5 MM

SECTION DRAWINGS

EAVES FLASHING WOODGRAIN



SPECIFICATION

Product	Eaves Flashing Woodgrain
Section	165 x 175 x 25 x 25 mm
Length	3.0 m
Thickness	0.5 mm
Finish	Polyester with an embossed woodgrain texture at 0.5 mm, 25 micron nominal, on a galvanised steel substrate
Colours	Ash, Natural and Walnut
Safety welt	8 mm, turned under and pressed flat, so no cut edge shows on the colour face
Inside bend radius	1.0 mm at 0.5 mm
Weight per metre	0.5 mm: 1.59 kg/m
Fixing	22 mm stitcher screws through the crowns of the sheet, 400 mm maximum centres
Overlap	150 mm minimum where lengths join
Made by	Briarwood at Highbridge, Somerset, folded from flat steel on the flashing folder

SECTION AND GIRTH

Section	Girth (flat width)
165 x 175 x 25 x 25 mm	406 mm

Sections are drawn from the CAD at 0.5 mm steel.

Weight per metre = girth × steel thickness × 7.85 kg/m^2 per mm. Steel only; the paint is not counted.

BRIARWOOD PRODUCTS LTD
Briarwood Business Park, Commerce Way
Walrow Industrial Estate, Highbridge, Somerset, TA9 4AG
Company number 02900287

Tel: +44 (0)1934 641446
sales@briarwoodproducts.co.uk
www.briarwoodproducts.co.uk
VAT registered number 634 4360 51